

## Datasheet SDT 270 (Standard & ATEX version)

### Description:

The SDT270 ultrasound detector features multiple significant innovations dedicated to the improvement of predictive maintenance programs. Manufactured by and for maintenance professionals, the SDT270's innovations show our commitment to the production of intelligent and progressive instruments.

Not only is the SDT 270 the first portable ultrasound detection device to include both a built-in temperature sensor and a laser tachometer, but it's also the first one to feature an onboard SQL database to capture and manage survey data.




### Main features:



- Available in Standard or ATEX version
- Measures broadband ultrasound signals up to 100 kHz bandwidth
- Realizes data acquisition with a 256 kHz sampling frequency
- Uses long-duration time sampling and data streaming
- Integrates built-in thermometer and tachometer with a laser
- Includes a SQL database
- Includes an Operator logging in
- Insures full measurement traceability from Operator to sensor
- Warns the Operator when an alarm is triggered
- Is IP (Internet) addressable
- Is remotely controlled and operated
- Incorporates 2 measurement channels

### Specifications:

| General                |  |  |
|------------------------|--|--|
| Function               |  | Handheld multifunction data collector  |
| Operable with          |  | Provided sensors   |
| Software compatibility |  | Ultranalysis Suite 3, DataDump,  |
| Versions               |  | FUR270, FUR270A (ATEX)   |
| ATEX marking           |  | CE 0029 Ex II(1) G Ex ia II C T3/T2 Ga   |
| Input interface        |  | 2 channels via 7 pole LEMO connector   |
| Built-in sensors       |  | Ultrasonic airborne sensor<br>Temperature sensor (optional)<br>Tachometer (optional) |
| Display                |  | Graphic LCD with backlighting (128 x 64 pixels)                                      |
| Supported languages    |  | Multilingual   |

|   |         |  |
|---|---------|--|
| Keyboard                                  |         | 12 functions keys  |
| Measuring frequency range                 | kHz     | Up to 100  |
| Signal amplification                      | dB      | from 0 to +90 by step of +10   |
| Typical measuring range                   | dB      | -13 to +99.9   |
| Resolution                                | digits  | 0.1  |
| Refresh RMS period time                   | ms      | 250  |
| Raw sampling frequency                    | ksps    | 256  |
| ADC Resolution                            | bits    | 16   |
| Response time                             | ms      | < 10   |
| Auto power down                           | min     | Customizable   |
| Communication                             |         | USB interface<br><br>Ethernet 10/100 Mbps (only on standard version, not available on ATEX version)  |
| <b>System features</b>                    |         |  |
| Firmware                                  |         | Regular updates  |
| Data logger (upgradable)                  |         | <p><b>SDT270 SS &amp; SD with DataDump software:</b></p> <ul style="list-style-type: none"> <li>100 measurement nodes for a total capacity of 4 000 measurements</li> </ul> <p><b>SDT270 DD with DataDump software:</b></p> <ul style="list-style-type: none"> <li>100 measurement nodes for a total capacity of 4 000 measurements</li> <li>dynamic measurements: 6 675 seconds with US sensor</li> </ul> <p><b>SDT270 SU used with Ultranalysis Suite 3:</b></p> <ul style="list-style-type: none"> <li>more than 10 000 measurement nodes with static data</li> </ul> <p><b>SDT270 DU used with Ultranalysis Suite 3:</b></p> <ul style="list-style-type: none"> <li>static measurements: more than 10 000 measurement nodes</li> <li>dynamic measurements: 6 675 seconds with US sensor</li> </ul> |
| Recording formats                         |         | Static or Dynamic measurements (wavefiles, heterodyned signals at 8ksps)   |
| Max acquisition time per recording        | s       | 80 seconds at 8 ksps   |
| <b>Environmental</b>                      |         |  |
| Standard temperature range                | °C (°F) | -15 to +60 (5 to 140), non-condensing  |
| Ambient temperature range on ATEX version |         | -Class T2 / -15 °C to +60 °C / 5 °F to 140 °F<br><br>-Class T3 / -15 °C to +48 °C / 5 °F to 118 °F   |
| IP rating                                 |         | IP 30  |
| Approvals                                 |         | EMC compliant (directive 2014/30/EU)<br><br>ROHS compliant (directive 2011/65/EU)<br><br>LVD compliant (directive 2014/35/EU)<br><br>ATEX compliant (directive 2014/34/EU ) ; for the concerned version  |

|  |         |   |
|--|---------|---|
| Type approval from Lloy's register<br>(Certificate No. 17/30042 for Sherlog kit)   |         | Application : Verification of marine, offshore, and industrial weather tightness of hatch covers, doors, ramps, and windows   |
| <b>Mechanical</b>  |         |   |
| Housing material   |         | Extruded aluminum   |
| Protective holster   |         | Fluorosilicone, hydrocarbon-resistant   |
| Dimensions   | mm (in) | L x W x H : 226 x 90 x40 (8.9 x 3.5 x 1.6)  |
| Weight   | g (oz)  | 830 (29.3), battery and holster included  |
| Audio connector  |         | 6.5 mm jack   |
| Utility connector<br><br>(Cannot be used as a recharging port)   |         | USB Mini<br>(import/export data and update the firmware)  |
| <b>Battery</b>   |         |   |
| Battery pack   |         | Internal, rechargeable type NiMh  |
| Nominal capacity   | mAh     | 4000  |
| Voltage  | V       | 4.8   |
| Autonomy   | hours   | ~ 8   |
| Battery charger<br><br>(Please only used the provided charger)   |         | specific for SDT2XX NiMH battery pack<br>Power supply: 230 or 110 VAC +15% /-10% - 50/60Hz<br>Output voltage: +4.0 or 8.5 V DC (depends on operating mode)<br>Current: 1000 mA maximum<br>Recharge time: 5 to 6 hours typical in fast mode / 12 to 14 hours typical in slow mode<br>Protection: temperature protected; limit set at 60°C / 140 °F |
|  Battery charge of the SDT2XX ATEX must exclusively be performed outside potentially explosive environments. |         |   |
| <b>Audio</b>   |         |   |
| Operable with  |         | provided headset only (Peltor) :25 dB NRR with Peltor quality headphones  |
| Safety note  |         | Compliant with directive 2003/10/EC, noise exposure, health and safety protection using SDT devices and provided headsets   |
| Maximum audio output (protection)  | dB SPL  | +83 with SDT provided headset   |
| <b>Ultrasound measurement</b>  |         |   |
| Operable with  |         | SDT provided sensors/ built-in sensor (intUS1)<br><br>SDT ATEX sensors are only intended for use with ATEX instruments  |
| Sensitivity  |         | Class I exceeding ASTM 1002-11 requirements for gas leak detection with the built-in sensor   |
| Reference calibrated voltage   |         | $V_0 = 1 \mu V = 0 \text{ dB}\mu V$   |
| dB scale definition  |         | $X \text{ dB}\mu V = 20 \log(V/V_0)$ where V is measured then converted in X dB $\mu V$   |
| Typical measuring range  |         | from -10 dB $\mu V$ to 109 dB $\mu V$ using gain function<br>*depending on the sensing capacity of the sensor   |
| Sampling rate  | ksps    | 8 (heterodyned)   |
| Available filters  |         | Determined from the sensor recognition  |
| Indicators   |         | RMS, Max RMS, Peak and Crest Factor   |

|  |         |   |
|--|---------|---|
| Refresh rate   | ms      | 250   |
| Audible rendering  |         | Indirect via heterodyne method  |
| Mixer frequency  | kHz     | Tunable, default mixer from the sensor recognition to provide the best audible rendering  |
| <b>Vibration measurement</b>   |         |   |
| Compatible accelerometers  |         | Any 100mV/g ICP accelerometer   |
| Vibration units  |         | Accelerometry [g] and velocity [mm/s, ips]  |
| Measuring range  |         | Up to 20 g peak   |
| Available filters  |         | [10 Hz-1 kHz] at 8 ksps<br><br>[10 Hz-10 kHz] at 32 ksps  |
| Indicators   |         | RMS velocity, RMS acceleration, Peak acceleration, Crest Factor   |
| Refresh rate   | ms      | 250   |
| Audible rendering  |         | Direct  |
| <b>Temperature module (on-board)</b>                                   |         |   |
| Type   |         | High precision non-contact infrared thermometer   |
| Available units  |         | Celsius, Fahrenheit, Rankine, Kelvin  |
| Adjustable emissivity  |         | [0.01 to 1], 1 by default   |
| Measuring range  | °C (°F) | -70 to +380 (-94 to +716)   |
| High accuracy in a wide temperature range (0°C to 50°C--32°F to 122°F) | °C      | ± 0.5 °C  |
| Field of view (attenuation of 50%)                                     |         | 10° : cover a spot of 10 cm (1/3 ft) at a distance of 10 cm (1 ft)  |
| <b>Rotational speed module (on-board)</b>                              |         |   |
| Type   |         | Optical sensor  |
| Units  |         | RPM/CPM and Hz  |
| Type of source   |         | Red laser Class II  |
|  |         |    |
| Cautions   |         | <ul style="list-style-type: none"> <li>• Never look directly to the laser beam</li> <li>• Never point the laser beam at a person's eye</li> <li>• Do not aim the laser at specular reflective surfaces</li> <li>• Never view the laser using an optical instrument</li> </ul> |
| Recommended measuring distance   | mm (in) | 50 to 2000 (2 to 80)  |
| Measuring range  |         | ~10 to 99 999 RPM<br><br>*a reflective band must be stick on the rotating part to perform a measurement   |
| <b>Warranty</b>  |         |   |
| Lifetime warranty  |         | Visit <a href="http://www.sdtultrasound.com">www.sdtultrasound.com</a> for details  |

NB: Additional details are available from the download section of SDT website

## Compatibilities:

SDT 270 receiver is designed to work in combination with the provided sensors and the associated cables of predefined length.

| Sensors denomination                                     | type                  | Non-exhaustive pillar applications         |
|--|-----------------------|--|
| RS1T (in ATEX version) /RS2T                             | contact               | Mechanical, steam trap                     |
| RS1NL 100-300-500 (in ATEX version)<br>RS2NL 100-300-500 | contact               | Mechanical, steam trap, valves, hydraulics |
| LUBESense1   | contact               | Lubrication                                |
| FLEXEX (ATEX version) /FLEX ID2                          | airborne              | Leak, electrical, tightness                |
| PARADISH2 (Standard or ATEX version)                     | airborne              | Electrical                                 |
| TTS1/TTS2 (in ATEX version)                              | airborne,<br>enclosed | Tightness for Tank tests                   |
| 100mV/g ICP accelerometer (Hansford)                     | contact               | Mechanical                                 |

In addition, SDT 270 receiver is compatible with SDT softwares running on windows OS. The communication is ensured with the provided USB cable.

Make sure you always run the latest version of the software & firmware to take advantage of new features. Please refer to the user manual for instructions on how to proceed.

## Safety recommendations:

- Do not expose the equipment to rough handling or heavy impacts
- Please read the user manual carefully before first use
- Opening the housing of the instrument may result in hazardous mishandling and voids warranty
- The equipment should not be used in areas where there is a risk for explosion
- Do not expose the equipment to high humidity or direct contact with water
- All repair work must be performed by SDT or authorized services
- Using any other headset or any sensor than the one supplied with the instrument can cause internal damage to the device

|             |                |   |                 |
|-------------|----------------|---|-----------------|
|             |                |   |                 |
|             |                |   |                 |
|             |                |   |                 |
| 4           | CMA 2021/07/20 | New layout                                      | BDG             |
| 3           | CMA 2021-22-01 | Correction du nobo, ajout temp range atex T2/T3 | CGR             |
| 2           | BDK 2015-07-13 | Ethernet not available on ATEX version          | GEL             |
| 1           | JPD            | Original version                                | GEL             |
| <b>Ver.</b> | <b>Editor</b>  | <b>Nature of modification</b>                   | <b>Verified</b> |

*The information herein is believed to be accurate to the best of our knowledge.  
Due to continuous research and development, specifications are subject to change without prior notice.*